

Dishwasher GS HH 500LR



Description

Features

- | | |
|------------------------------------|---------------------------|
| • Tray size max.: | 470 x 365 mm |
| • Plate height max.: | 365 mm |
| • Door double-walled: | Yes |
| • Can be fitted below the counter: | Yes |
| • Glasses height max.: | 325 mm |
| • Power load: | 5,4 kW 400 V 50 Hz |
| • Equipment connection: | 3 NAC |
| • Boiler heater: | 3 kW |
| • Tank heater: | 2,1 kW |
| • Water outlet: | yes |
| • Dry-run protection: | Yes |
| • Control lamp: | ON/OFF
Rinsing process |
| • ON/OFF switch: | Yes |
| • Lye pump: | Yes |
| • Water softener: | No |
| • Clear rinsing dosing pump: | Yes |

► Continue on the next page

Dishwasher GS HH 500LR

- Door contact switch: Yes
- Safety thermostat: Yes
- Cleaning agent dosing pump: Yes
- Basket dimensions: 500 x 500 mm
- Run-time: 60 / 180 seconds
- Output / hour max.: 60 baskets
- Self-cleaning: No
- Double-walled: No
- Cold rinsing: No
- Tank volume: 21 litre(s)
- Water pressure: 2 - 4 bar
- Water supply: G 3/4"
- Including: 1 plate basket
1 universal basket
1 cutlery basket
- Number of wash programs: 2
- Material: Stainless steel
- Important information: -
- Properties: DuoFlo pump (less pump loss)
Electronic thermo-stop
Energy-Saving-System (boiler is only active when necessary)
- Water consumption at 2 bar: 2.4 litres / wash cycle
- Size: W 580 x D 600 x H 820 mm
- Weight: 49.2 kg

