

Induction cooker IK 70dpZ-EB



Description

You can't get more flexible than this: This induction cooker with its removable control panel is suitable for use as a table-top appliance or for being built into a buffet counter. Its 7000 W of power can be distributed over the two hobs as required – the left-hand hob, with up to 5000 W, is ideal for fast poaching and hot roasting.

5000 W

3500 W

60 °C to 240 °C

Next to each other

Features

- Power with power switching, left hob:
- Temperature range:
- Arrangement of the hobs:
- Output hob left max.:
- Output hob right max.:
- Diameter hob left:
- Diameter hob right:
- Number of temperature levels:
- Intervals temperature setting:
- Power load:
- Equipment connection:
- Control unit:
- Number of hobs:
- Type of hobs: Control lamp:

3500 W 235 mm 235 mm 10 20 °C 7 kW | 400 V | 50/60 Hz 3 NAC Toggle 2 Induction Output Temperature Pot recognition



Total power: 7000 W



- 2 hobs next to each other can be turned on and off separately
- ✓ Power per hob: 3500 W



- Power switching of left hob to 5000 W
 Power of right hob: 2000 W
- Can be used as a table-top or built-in appliance
 - Ideal for custom, needs-based installation



Removable control panel
 Regulation of power and temperature

Continue on the next page



Code-No. **105893**



Induction cooker IK 70dpZ-EB

Size cerane surface:	W 645 x D 315 mm
Overheating protection:	Yes
Digital display:	Yes
ON/OFF switch:	No
 Lock button (child protection): 	No
 Pot recognition: 	Yes
 Core temperature sensor: 	No
Colour:	Silver
	Black
 Material hob: 	Glass
 Regulation of: 	Output
	Temperature
Material:	Stainless steel
 Important information: 	-
 Number of output levels: 	11 / 10
• Timer:	No
Properties:	Separate control panel, cable length 0.85 m
• Max. output of right hob with power switching:	2000 W
Can be installed:	Yes
• Size:	W 715 x D 485 x H 140 mm
Weight:	14.8 kg
-	-







Induction cooker IK 70dpZ-EB Add on Products

